

LCP150T-1H36V

Summary

LCP150T-1H36V is a constant voltage mode output LED driver. The driver supports leading edge (Triac) and trailing edge (ELV) dimmer, and can be compatible with the systems of various brands (Philips, Panasonic, Lutron, Simon, ABB,Bunge, Siemens etc.) to achieve a smooth dimming effect.

Product Feature

- Single-channel constant voltage output, 4.17A Max.
- Support Leading edge (Triac) and Trailing edge (ELV) Dimmer
- Dimming range from 40VAC to 240V AC
- Dimming effect smooth, no flicker
- Over current protection; Short circuit protection; Over voltage
- Suitable for indoor LED lighting application

Application

For LED constant voltage strip light only



LED Strip Light




LED Tube




Technical Parameters

Model	LCP150T-1H36V		
Input	Efficiency	≥89%@230VAC, Full load	
	Voltage	220VAC-240VAC	
	Frequency	50/60Hz	
	Power Factor	≥0.98@230VAC, Full load	
	Current	0.85Amax@230VAC, Full load	
	THD	<10%@230VAC, Full load	
	Dimming voltage range	40-240VAC	
	Inrush Current	Cold start,24.7A@230VAC 26us	
	No load power	<2W	
Output	Current/Voltage/Power	4.17A/36VDC/150W	
	No load output voltage	36VDC±5%	
	Channel	1	
	Voltage Accuracy	±3%	
	Turn On Delay Time	NA	
Function	Dimming Mode	Triac	ELV
	Dimming range	1%-100%	
Protection	Over load	Limit the output to 110% to 150% of the rated power	
	Short Circuit	Hiccup, recovers after fault condition is removed	
	Over voltage	When the output voltage is exceeded, the output current decreases and, recovers automatically when the load is reduced.	
Safety&EMC	Surge	L-N:2KV	
	Withstand Voltage	I/P-O/P: 3000VAC/1min/5mA	
	Safety standards	EN61347, GB19510	
	EMI emission	EN55015, EN61000-3-2	
	EMC Immunity	EN61000-4-2, 3, 4, 5, 6, 8, 11; EN61547	
Others	Working Temp.	-20°C~50°C	
	Storage Temp.; Humidity	-40°C~85°C, 20-90%RH	
	Tc	90°C	
	Material	PC	
	IP Rating	IP20	
	Lifetime	50,000h@tc:90°C	
	Warranty Condition	5 years	
	Switch Cycle	>25,000 times	
	Packing Size	Net weight: 730g±5%/PCS; 25PCS/Cartron;19kg±5%/Cartron; Carton Size:377*241*196mm(L*W*H)	
	Dimension	360*40*32mm (L*W*H)	


Dimension(mm)




Wiring Diagram




Dimming Curve




Eff. vs Load




PF vs Load



Derating Curve




THD vs Load



Cautions

- 1.The product shall be installed and serviced by a qualified person.
- 2.This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
- 4.Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.For safety consideration, PVC or rubber cord of 0.75-1.5mm² is recommended for input and output terminal(s) . Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.
- 8.No insulation between dimming circuit and LV circuit



※ The contents of this manual are updated without prior notice. If the function of the product you are using is inconsistent with the instructions, the function of the product shall prevail. Please contact us if you have any questions .

LCP150T-1H36V

概述

LCP150T-1H36V 是一款恒压输出 LED 调光驱动器。这款驱动器支持前沿切相和后沿切相调光器，可以与多品牌系统(飞利浦, ABB, 路创, 西门子, 西蒙, 松下等)配合使用，实现平滑调光的效果。

产品特点

- 单通道恒压输出，最大输出电流为 4.17A
- 支持前沿 (Triac) 和后沿(ELV)调光
- 调光电压范围 40VAC- 240VAC
- 调光曲线平滑，无抖动
- 过流保护；过压保护；短路保护
- 适用于室内 LED 灯具

应用

仅用于LED恒压灯带



LED灯带




LED硬灯条




技术参数

型号	LCP150T-1H36V		
输入	效率	≥89%@230VAC, 满载	
	电压	220VAC-240VAC	
	频率	50/60Hz	
	功率因素	≥0.98@230VAC, 满载	
	电流	0.85Amax@230VAC, 满载	
	THD	<10%@230VAC, 满载	
	调光电压范围	40-240VAC	
	浪涌电流	冷启动,24.7A@230VAC 26us	
	空载功耗	<2W	
输出	电流/电压/功率	4.17A/36VDC/150W	
	空载电压	36VDC±5%	
	通道	1	
	电压精度	±3%	
	启动延时	NA	
功能	调光方式	前沿	后沿切相调光
	调光范围	1%-100%	
保护	过载	将输出功率限制在额定功率的 110%-150%	
	短路	打嗝，去除故障后自恢复	
	过压	当超过输出电压时，输出电流减小，负载减小时自动恢复	
安规和电磁兼容	浪涌	L-N:2KV	
	耐压	I/P-O/P: 3000VAC/1min/5mA	
	安全标准	EN61347, GB19510	
	电磁兼容	EN55015, EN61000-3-2	
	EMC抗扰度	EN61000-4-2, 3, 4, 5, 6, 8, 11; EN61547	
其它	工作温度	-20°C~50°C	
	储存温度、湿度	-40°C~85°C, 20-90%RH	
	tc	90°C	
	材质	PC	
	防水等级	IP20	
	寿命	50,000小时@tc:90°C	
	质保	5年	
	开关周期	>25,000次	
	包装重量	净重:730g±5%/PCS; 25PCS/箱; 19kg±5%/箱; 外箱尺寸:377*241*196mm[长*宽*高]	
	尺寸	360*40*32mm （长*宽*高）	


产品尺寸




应用接线图




调光曲线




效率曲线




PF vs 负载



降额曲线




THD vs 负载



注意事项

1. 本产品请由具有专业资格的人员进行调试安装。
2. 本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
3. 良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
4. 请检查使用的LED电源输出电压电流，是否符合产品要求。
5. 出于安全考虑，推荐输入和输出(信号端除外)用0.75-1.5mm²PVC或橡胶线缆，并确保接线牢固，以免电线过热或接触不良触发事故。扁平电源线不适用。
6. 通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
7. 如果发生故障，请勿私自维修；如果有疑问，请联系供应商。



※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。