

LCP75M-2W24V (Product No.:101200060201)

Summary

LCP75M-2W24V is a constant voltage mode output LED driver, adjustment of brightness and colour temperature.

Product Features

- Double channel constant voltage output, output Current 3.125A Max
- Support RDM/DMX512 dimming signal
- Dimming range from 0.1-100%
- Wide range voltage Input 120-277VAC
- High efficiency: up to 92%
- High PF:0.98
- Dimming effect smooth, flicker free
- Output short circuit protection , Overload protection

Application

For LED constant voltage strip light only



LED Strip Light




LED Tube




Technical Paramaters

Model	LCP75M-2W24V	
Input	Efficiency	92%@230VAC,Full load
	Voltage	120VAC-277VAC
	Frequency Range(Hz)	50/60Hz
	Power Factor	0.98@230VAC,Full load
	THD(full load)	10%@230VAC, Full load
	AC Current(max)	0.39Amax@230VAC
	Inrush Current(max)	Cold start,40A@230VAC
Output	Current(mA)/Voltage (VDC) Power(W)	3.125A/24VDC/75W
	Channel	2
	Voltage Tolerance	±3%
	Standby power	<0.5W
	No load output voltage	24VDC±3%
	Turn on delay Time	<0.5s, at230Vac (When the light begins to shine)
Function	Dimming Type	RDM/DMX512
	Dimming Range	0.1%-100% Dimming to off
Protection	Over load	Hiccup, recovers after fault condition is removed
	Short Circuit	Hiccup, recovers after fault condition is removed
Safety&EMC	Surge	L-N:2KV
	Withstand Voltage	I/P-O/P: 3000VAC/1min/5mA
	Safety standards	EN61347, GB19510
Others	Working Temp.	-20°C~50°C
	Storage Temp., Humidity	-40°C~85°C, 20-90%RH
	tc	75°C
	Material	PC
	IP Rating	IP20
	Lifetime	50,000h@tc:75°C
	Warranty Condition	5 years
	Switch Cycle	25,000 times
	Packing(weight)	Net weight: 340g±5%/PCS; 50PCS/Cartron;17.5kg±5%/Cartron; Carton Size: 434*302*174mm(L*W*H)
	Dimension	295*40*32mm (L*W*H)


Dimension(mm)




Wiring



Dimming Curve



Derating Curve



Cautions

- 1.This product should be installed by qualified personnel.
- 2.This product is non waterproof, need to avoid sun and rain.In case of outdoor use, please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation conditions extend product life. Please install the product in a well-ventilated environment.
- 4.Please make sure LED power supply output voltage, current is used to meet the product requirements.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.Due to safety concerns, PVC or rubber cord of 0.75- 1.5mm² is recommended for input and output terminal(s)(excluding signal terminals). Flat power cord is not suitable.Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.In case of malfunction, do not repair it yourself.

LCP75M-2W24V (产品代码:101200060201)

概述

LCP75M-2W24V是一款恒压输出LED调光驱动器，驱动支持调光调色。

产品特点

- 双通道恒压输出，最大输出电流3.125A
- 支持 RDM/DMX512信号
- 调光范围从 0.1-100%
- 宽电压输入120-277VAC
- 高效率:达到92%
- 高PF:0.98
- 调光曲线平滑，无频闪
- 输出短路保护，过载保护

应用

仅用于LED恒压灯带



LED灯带




LED硬灯条




技术参数

型号	LCP75M-2W24V	
输入	效率	92%@230VAC, 满载
	电压	120VAC-277VAC
	频率	50/60Hz
	功率因素	0.98@230VAC, 满载
	THD	10%@230VAC, 满载
	电流	0.39Amax@230VAC
	浪涌电流	冷启动,28A@230VACC
输出	电流/电压/功率	3.125A/24VDC/75W
	通道	2
	电压公差	±3%
	启动延时	<0.5s, at230Vac
功能	调光方式	RDM/DMX512
	调光范围	0.1%-100% 变暗直至关闭
保护	短路	打嗝，关闭输出，排除故障后自恢复
	过载	打嗝，关闭输出，排除故障后自恢复
安全&电磁兼容	浪涌	L-N:2KV
	耐压	I/P-O/P: 3000VAC/1min/5mA
	安全标准	EN61347, GB19510
其它	工作温度	-20°C~50°C
	储存温度、湿度	-40°C~85°C, 20-90%RH
	tc	75°C
	材质	PC
	防水等级	IP20
	寿命	50,000小时@tc:75°C
	质保	5年
	开关周期	25,000次
	包装尺寸(重量)	净重: 340g±5%/PCS; 50PCS/Carton; 17.5kg±5%/箱; 外箱尺寸: 434*302*174cm[长*宽*高]
	尺寸	295*40*32mm (长*宽*高)


尺寸(mm)




接线图



调光曲线



降额曲线



注意事项:

- 1、本产品请由具有专业资格的人员进行调试安装。
- 2、本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
- 3、良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
- 4、请检查使用的LED电源输出电压电流，是否符合产品要求。
- 5、出于安全考虑，推荐输入和输出（信号端除外）用0.75-1.5mm² PVC或橡胶线缆，并确保接线牢固，以免电线过热或接触不良触发事故。扁平电源线不适用。
- 6、通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
- 7、如果发生故障，请勿私自维修；如有疑问，请联系供应商。

※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。